

Heat Detector

Type: TF 180-PUR

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.



Characteristics:

- Manufacturer: EGON HARIG GmbH
- P/N: 80 793
- Suitable for fire detections
- Robust design, oil resistant cable
- Water- and dustproof, when cable connectors (m / f) are mated and screwed
- "Alarm"-set point (variable*) max 180 °C
- Delivery: incl. Mounting-Kit and Mounting-Instruction
- Only for connection to Fire Detection and Extinguishing Panels and for Evaluation Units of Temperature-Measurement and Extinguishing-Agent-Release Systems of Co. EGON HARIG GmbH

* The temperature at which an alarm should be triggered, will be set up fixed in the Fire Detection and Extinguishing Panel or in the Evaluation Unit of the Temperature-Measurement and Extinguishing-Agent-Release System.

Technical Data:

Length (without connection cable)	: approx. 77 mm (±1 mm)
Width (incl. mounting nuts, without connection cable)	: max. 25 mm
Weight (without Mounting-Kit)	: approx. 180 g
Length of connection cable (without cable connector)	: approx. 1.5 m
Housing material	: V2A / High-PEEK
Protection	: IP 68
Operating temperature range**:	-25 °C up to +90 °C
Connection type	: cable connectors (f) and female spade connectors (components of Mounting-Kit)
Mounting	: with attached mounting nuts in a borehole with a diameter of d = 14.5 mm

** Operating temperature range of connectors: -20 °C up to +70 °C

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date 08/14/2019

Version 0

EGON HARIG GmbH
 Gewerbering 4 • D-22113 Oststeinbek
 Tel./Phone: +49 (0)40 713752-0
 Telefax: +49 (0)40 713752-24
 E-Mail: egonharig@egonharig.de
 www.egonharig.de www.flamtron.de

Catalog sheet No

4.19226-1

Page 1 of 1